


TFT LCD Monitor

17.0" TFT Color LCD Monitor
17.0" TFT Color LCD Touch Monitor



MITSUTECH
INTERNATIONAL CORP



Model Selection

MT1700AVU 15 Pin D-Sub VGA PC graphic
Audio Stereo Speaker
Video Composite and
S-video Input
USB

MT1700AVU/Tx Optional Touch Screen
MT1700AVU/TC for Capacitive

Main Features

- ★ High Quality Image
- ★ Build-in Stereo Speaker
- ★ PAL/NTSC/SECAM Video Input
- ★ USB function
- ★ User Friendly OSD
- ★ Wall, Free-arm Mountable



MT1700AVU MT1700AVU/TC

■ Specifications

Model		MT1700AVU
LCD	Screen Size	17.0" (355.6 cm) Diagonal.
	Panel Type	TFT active matrix
	Number of Pixel	1280 x 1024 (UXGA)
	Pixel Pitch	0.264 mm x 0.264mm
	Display Area (W x H)	13.30" x 10.64" (337.92 x 270.336mm)
	Surface Treatment	Anti-glare and hard coat 3H ON LCD surface
	Colors	16millions
	Brightness	250 cd /m ²
	Contrast	400:1(Typ.)
	Response Time	45ms
Input Signals	Video Signal	RGB Analog, 0.714 Vp-p, 75 Ω
	Synchronization	VGA-UXGA, NTSC/PAL/SECAM
	Horizontal Frequency	25 ~79.97 KHz,
	Vertical Frequency	56.0 ~ 86 Hz
Connector	Video Signal	15- pin D-SUB
	NTSC/PAL Video-in	RCA Connector x 2; S-Video connector x 1
	NTSC/PAL Video-out	RCA Connector x 1
	USB	Up stream Port x 1; Down stream x 4
Audio	Line in	Stereo (Mini Jack x 1)
	Line out	Stereo (Mini Jack x 1)
	Speaker	Stereo (3Watt x 2)
External Control	Switch	Power Switch, Choice of Input Ports,
	On-Screen Display	Brightness, Contrast, Color Control(R/G/B), Phase, Audio Control, Horizontal Size, Horizontal Position, Vertical Position, Auto Adjustment, Expansion, Recall, Reset, OSD Menu Position OSD Language (English, Japanese)
Touch Panel (Optional)	Type	Capacitive
	Electrical Resolution	1024 x 1024
	Response Time	15 ms
	Communication System	Serial RS232
	Durability	Over 20 million times
	Accuracy	< ±1% error
Environment	Temperature	Operating: 0°C to +50°C Storage: -20°C to +60°C
	Humidity	8~95%RH (Non Condensing)
Power Supply		Input AC100-240V 50/60 Hz, Output: DC 12V
Power Consumption		45W(Max.) Stand by: 5W (Max.)
Power Management		VESA DPMS
Physical	Dimensions (W x H x D)	16.97"x17.4"x6.0" (431x442x153mm)
	Weight	18.74Lbs (8.5Kgs)
Plug & Play		DDC2B (VESA Standard)
Other Features		VESA Holes standard 75 x 75 mm
Accessories		AC Adapter & Cord, RGB Cable, Audio Cable, Video Cable, Operating Manual
Options		Touch Screen
Limited Warranty		One Year on Parts and Labor

- Features and Specifications are subject to change without prior notice